

Application for United States Patent

Title: System and Method of Autodialing for Long-Distance Access

Inventors: David Matthew Smith (Citizenship U.S.A.)

929 Westbrook Drive

Plano, TX 75075

Agent: Robert H. Frantz, 42,553

P.O. Box 23324

Oklahoma City, OK 73123-2334

U.S.A.

TECHNICAL FIELD OF THE INVENTION

This invention relates to autodialers, specifically to autodialers that dial long-distance access codes.

5 CROSS-REFERENCE TO RELATED APPLICATIONS

AND

INCORPORATION BY REFERENCE

10 This application is a non-provisional application based upon the provisional application entitled "System and Method of Autodialing for Long-Distance Access", filed on September 10, 1999, by David Matthew Smith, docket number DMS-099-001, now application serial number 60/153,039. Benefit under Title 35 USC §119(e) is hereby claimed for this related application, and it is incorporated by reference in its entirety including figures.

15 FEDERALLY SPONSORED RESEARCH AND DEVELOPMENT STATEMENT

This invention was not developed in conjunction with any Federally-sponsored contract.

MICROFICHE APPENDIX

Not applicable.

20

BACKGROUND OF THE INVENTION

The deregulation of long distance telephone service has led to increased competition among service providers. In order for this competition to have value to the consumer, the consumer must be able to easily use different services. For this reason, local telephone companies are required to provide access to any long distance provider by means of an access prefix dialed before the long distance number. However, remembering the prefix and dialing the extra digits are inconveniences to the telephone user, and these inconveniences tend to inhibit many people from trying new services. Thus, more people would take advantage of competitive long distance providers, and competition would be further stimulated, if a convenient means could be provided of dialing the access code whenever any user in a household or small office wanted to place a long distance telephone call.

U.S. Patent 5,644,633 to Kaufeld, *et al* discloses an autodialer intended to automatically modify a dialed number that meets a preprogrammed criterion, such as 1+ten digits. The invention stores the dial string and, if it meets the criterion disconnects by means of relays the line to the central office (on hook), reconnects the line (off hook), and redials the number along with whatever modifications or prefixes have been previously programmed into the invention. The temporary disconnect signals the central office that the call was aborted, allowing the invention to redial with the modified number.

One disadvantage of this "store and forward" approach is that the autodialer must be connected between the central office and any telephone that is intended to use it. In a

residence, for example, several telephone extensions commonly share one telephone line.

If a “store and forward” autodialer is to be used with all such extensions, then the residence wiring must be physically disconnected from the wire to the telephone company, and the autodialer installed between the two sets of wiring. This is not a task
5 that consumers will readily undertake.

Other disadvantages should be apparent. The complexity and power required by relays, for example, may make it impractical for such a device to be small and battery-powered with an acceptable battery life.

U.S. Patent 5,859,896 to Howard B. Rosen discloses an autodialer that connects in
10 parallel with the other telephone extensions in a residence, thus avoiding the installation problems of a “store and forward” autodialer. This invention, however, always dials the preprogrammed dialing prefix whenever a telephone extension goes off hook. The prefix might be a local area code or a long distance access code. If the user wishes to dial a number without the prefix such as a local number he must “flash” the telephone hook
15 switch and then redial. The invention senses the “flash” and does not dial the prefix again. One disadvantage of this approach is that the “flash” must be timed by the user to be long enough so that the central office treats the automatically-dialed prefix as an aborted call, while not so long that the autodialer does so also. It will be readily apparent that this method is not well-suited for many consumers, and would probably cause great
20 annoyance.

The present art provides no method for dialing long distance access codes that can be considered a distinct improvement over manual dialing. Therefore, there is a need in

5

1971	1972	1973	1974	1975	1976	1977	1978	1979	1980	1981	1982	1983	1984	1985	1986	1987	1988	1989	1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100	2101	2102	2103	2104	2105	2106	2107	2108	2109	2110	2111	2112	2113	2114	2115	2116	2117	2118	2119	2120	2121	2122	2123	2124	2125	2126	2127	2128	2129	2130	2131	2132	2133	2134	2135	2136	2137	2138	2139	2140	2141	2142	2143	2144	2145	2146	2147	2148	2149	2150	2151	2152	2153	2154	2155	2156	2157	2158	2159	2160	2161	2162	2163	2164	2165	2166	2167	2168	2169	2170	2171	2172	2173	2174	2175	2176	2177	2178	2179	2180	2181	2182	2183	2184	2185	2186	2187	2188	2189	2190	2191	2192	2193	2194	2195	2196	2197	2198	2199	2200	2201	2202	2203	2204	2205	2206	2207	2208	2209	2210	2211	2212	2213	2214	2215	2216	2217	2218	2219	2220	2221	2222	2223	2224	2225	2226	2227	2228	2229	2230	2231	2232	2233	2234	2235	2236	2237	2238	2239	2240	2241	2242	2243	2244	2245	2246	2247	2248	2249	2250	2251	2252	2253	2254	2255	2256	2257	2258	2259	2260	2261	2262	2263	2264	2265	2266	2267	2268	2269	2270	2271	2272	2273	2274	2275	2276	2277	2278	2279	2280	2281	2282	2283	2284	2285	2286	2287	2288	2289	2290	2291	2292	2293	2294	2295	2296	2297	2298	2299	2300	2301	2302	2303	2304	2305	2306	2307	2308	2309	2310	2311	2312	2313	2314	2315	2316	2317	2318	2319	2320	2321	2322	2323	2324	2325	2326	2327	2328	2329	2330	2331	2332	2333	2334	2335	2336	2337	2338	2339	2340	2341	2342	2343	2344	2345	2346	2347	2348	2349	2350	2351	2352	2353	2354	2355	2356	2357	2358	2359	2360	2361	2362	2363	2364	2365	2366	2367	2368	2369	2370	2371	2372	2373	2374	2375	2376	2377	2378	23
------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	----

SUMMARY OF THE INVENTION

This invention provides a convenient long-distance access autodialer that connects in a parallel fashion to a telephone line and automatically dials a preprogrammed access code when the user dials the first "1" in a long distance number (i.e., "1" + area code + number). This invention dials the access code without the initial "1," which the user dials, and appends a "1" after dialing the access code, so that the user can continue dialing with the area code. This invention dials the access code as rapidly as the central office permits, so that the user perceives no inconvenient delay when dialing a long distance number.

This invention times the length of the "1" dialed by the user, so that if the "1," exceeds a preset time interval, such as one second, the prefix code is not dialed, permitting a simple means to defeat the autodialer for numbers such as "1411." This invention also times another preset interval after the initial "1," so that if further digits follow quickly, as from a speed-dialing telephone or FAX machine, the prefix code is not dialed.

Finally, this invention is very inexpensive to manufacture, and can be battery operable as an option, with a battery life on the order of a year or more.

In accordance with the present invention, an autodialer comprises a parallel connection to a telephone line, a means of detecting and identifying the first digit dialed when any telephone extension originates a call; means of timing short intervals such as digit duration; and, taking advantage of the fact that all long distance access codes begin with the digit "1," a means of automatically dialing the access code minus the beginning

English	Arabic	Arabic	English
1. I have a car	أنا أملك سيارة	أنا أملك سيارة	1. I have a car
2. The car is red	السيارة حمراء	السيارة حمراء	2. The car is red
3. I like the car	أنا أحب السيارة	أنا أحب السيارة	3. I like the car
4. The car is fast	السيارة سريعة	السيارة سريعة	4. The car is fast
5. I bought the car	أنا اشتريت السيارة	أنا اشتريت السيارة	5. I bought the car
6. The car is new	السيارة جديدة	السيارة جديدة	6. The car is new
7. I want a car	أنا أريد سيارة	أنا أريد سيارة	7. I want a car
8. The car is expensive	السيارة باهظة	السيارة باهظة	8. The car is expensive
9. I love my car	أنا أحب سيارتي	أنا أحب سيارتي	9. I love my car
10. The car is small	السيارة صغيرة	السيارة صغيرة	10. The car is small
11. I sold the car	أنا باعته	أنا باعته	11. I sold the car
12. The car is old	السيارة قديمة	السيارة قديمة	12. The car is old
13. I need a car	أنا أحتاج سيارة	أنا أحتاج سيارة	13. I need a car
14. The car is big	السيارة كبيرة	السيارة كبيرة	14. The car is big
15. I lost the car	أنا فقدت السيارة	أنا فقدت السيارة	15. I lost the car
16. The car is slow	السيارة بطيئة	السيارة بطيئة	16. The car is slow
17. I found the car	أنا وجدت السيارة	أنا وجدت السيارة	17. I found the car
18. The car is noisy	السيارة صاخبة	السيارة صاخبة	18. The car is noisy
19. I repaired the car	أنا أصلت السيارة	أنا أصلت السيارة	19. I repaired the car
20. The car is broken	السيارة معطلة	السيارة معطلة	20. The car is broken
21. I washed the car	أنا غسلت السيارة	أنا غسلت السيارة	21. I washed the car
22. The car is dirty	السيارة قذرة	السيارة قذرة	22. The car is dirty
23. I parked the car	أنا وقفت السيارة	أنا وقفت السيارة	23. I parked the car
24. The car is parked	السيارة وقفة	السيارة وقفة	24. The car is parked
25. I drove the car	أنا ساءت السيارة	أنا ساءت السيارة	25. I drove the car
26. The car is driving	السيارة تسير	السيارة تسير	26. The car is driving
27. I stopped the car	أنا أوقف السيارة	أنا أوقف السيارة	27. I stopped the car
28. The car is stopped	السيارة متوقفة	السيارة متوقفة	28. The car is stopped
29. I started the car	أنا أبدأ السيارة	أنا أبدأ السيارة	29. I started the car
30. The car is starting	السيارة تبدأ	السيارة تبدأ	30. The car is starting
31. I turned the car	أنا أدير السيارة	أنا أدير السيارة	31. I turned the car
32. The car is turning	السيارة تدور	السيارة تدور	32. The car is turning
33. I changed the car	أنا أغير السيارة	أنا أغير السيارة	33. I changed the car
34. The car is changing	السيارة تتغير	السيارة تتغير	34. The car is changing
35. I fixed the car	أنا أصلت السيارة	أنا أصلت السيارة	35. I fixed the car
36. The car is fixed	السيارة مصلوبة	السيارة مصلوبة	36. The car is fixed
37. I painted the car	أنا طليت السيارة	أنا طليت السيارة	37. I painted the car
38. The car is painted	السيارة ملونة	السيارة ملونة	38. The car is painted
39. I cleaned the car	أنا نظفت السيارة	أنا نظفت السيارة	39. I cleaned the car
40. The car is clean	السيارة نظيفة	السيارة نظيفة	40. The car is clean
41. I upgraded the car	أنا أتحسن السيارة	أنا أتحسن السيارة	41. I upgraded the car
42. The car is upgraded	السيارة محسنة	السيارة محسنة	42. The car is upgraded
43. I replaced the car	أنا أغير السيارة	أنا أغير السيارة	43. I replaced the car
44. The car is replaced	السيارة مبدلة	السيارة مبدلة	44. The car is replaced
45. I modified the car	أنا أعدل السيارة	أنا أعدل السيارة	45. I modified the car
46. The car is modified	السيارة معدلة	السيارة معدلة	46. The car is modified
47. I customized the car	أنا أخصص السيارة	أنا أخصص السيارة	47. I customized the car
48. The car is customized	السيارة مخصصة	السيارة مخصصة	48. The car is customized
49. I upgraded the car	أنا أتحسن السيارة	أنا أتحسن السيارة	49. I upgraded the car
50. The car is upgraded	السيارة محسنة	السيارة محسنة	50. The car is upgraded

BRIEF DESCRIPTION OF THE DRAWINGS

The figures presented herein when taken in conjunction with the disclosure, form a complete description of the invention.

5 FIGURE 1A shows the basic embodiment with discrete timers for marking the various timer intervals necessary, and a separate logic means for controlling the device's operation.

FIGURE 1B shows the method of operation for the basic embodiment.

10 FIGURE 2A shows a battery-powered embodiment in which most of the autodialer is powered down until a transient appears on the telephone line, a transient detector to turn power on, and separate logic and timers.

FIGURE 2B shows the method of operation for the battery-powered embodiment of FIGURE 2A.

15 FIGURE 3A shows the preferred embodiment battery-powered with the timers and control logic implemented in a microprocessor.

FIGURE 3B shows the method of operation of the preferred embodiment.

DETAILED DESCRIPTION OF THE INVENTION

Basic Embodiment

The basic embodiment of the present invention is shown in FIGURE 1A. A Telephone Loop 101 is a normal analog telephone line with one or more telephone instruments connected throughout a residence or small office. Telephone Loop 101 is extended to the invention by means of any convenient wiring, such as a standard RJ11-terminated telephone cord, where it connects to an AC Coupling 102. AC Coupling 102 comprises a transformer and a blocking capacitor, preventing flow of direct current through the loop when the autodialer is connected, and providing electrical isolation and longitudinal balance if the autodialer is powered from the AC mains. A DTMF Transmitter 103 is connected to AC Coupling 102 so as to be able to transmit DTMF digits to Telephone Loop 101. A DTMF Receiver 104 is connected to AC Coupling 102 so as to be able to sense and identify DTMF digits that are present on Telephone Loop 101 from any telephone instrument. DTMF Transmitter 103 and DTMF Receiver 104 can easily be the two halves of any readily available DTMF transceiver IC, such as the M8888 manufactured by the Teltone Corporation of Bothell, Washington.

An electronic Logic 105 operates DTMF Transmitter 103 and senses DTMF Receiver 104. An electronic Digit Duration Timer 106, Digit Interval Timer 107, and Next Digit Timer 108 are connected to Logic 105 so that Logic 105 may start and stop each timer and sense whether each timer has expired.

A Programmed Access Code 109 is a set of manually-operated switches, or an electronic memory that retains the desired long distance access code and is connected to

Logic 105 so that Logic 105 may retrieve the desired code and sequence it through Transmitter 103. If Access Code 109 is in the form of switches, the user can easily and quickly change long distance service by changing the code.

A Power Source 110 may be any convenient source of power suitable for the electronic components. However, this embodiment draws continuous power while monitoring Telephone Loop 101, and battery power will probably not be practical.

The method of the basic embodiment is shown in Figure 1B, which depicts the states and actions of Logic 105. A Wait State 20 indicates that the Autodialer is idle and waiting for the first digit to be dialed. Wait State 20 exits as soon as a DTMF signal is detected by DTMF Receiver 104, and Action 21 causes Digit Duration Timer 106 to start.

The autodialer now waits at Wait State 22. If this state exits because Digit Duration Timer 106 expired, or because the DTMF signal ended the digit was not a "1", then Action 26 starts Next Digit Timer 108 which is used in combination with Wait State 27 to determine when the user has finished dialing. If Wait State 27 exits because Next Digit Timer 108 expired, then the user is finished dialing and the Autodialer goes on to Wait State 20 to wait for the next number to be dialed. Thus, the autodialer ignores dialed numbers that do not begin with a "1", or that begin with a digit pressed for longer than the Digit Duration Timer interval, perhaps one second.

If Wait State 22 exits because the DTMF signal ended and the digit was a "1", then Action 23 starts Digit Interval Timer 107. The autodialer now goes to Wait State 24. If Wait State 24 exits because another DTMF signal was detected by DTMF Receiver 104, then the Autodialer proceeds to Action 26 to wait for the user to finish dialing.

Thus, the Autodialer ignores a dialed number when the digits come in rapid succession, as from some non-manual source such as a speed dialer. However, if Wait State 24 exits because Digit Interval Timer 107 expired, then Action 25 causes DTMF Transmitter 103 to dial Access Code 109, which comprises the seven digits of a long distance access code, with the leading "1" dialed at the end instead. The user then goes on to dial the rest of his number, while the Autodialer proceeds to Action 25 to wait for dialing to finish.

When the Autodialer determines that the dialing has finished, by exiting Wait State 27 because the Next Digit timer has expired, then it proceeds to Wait State 20 to wait for a new number.

Suppose the user wishes to dial a long distance number, such as "1-617-123-4567," and has Access Code 109 programmed for "1010555." The Autodialer idles at Wait State 20. The User presses "1" which causes the Autodialer to proceed through Action 21 to Wait State 22. If the user does not press the "1" key for an unnaturally long timer, then when the key is released the Autodialer proceeds to Action 23 and Wait State 24. If the user does not quickly press the next digit, the Autodialer proceeds to Action 25 and 26. The telephone company's Central Office receives the sequence "1 (user)-010555-1 (Autodialer)-617-12304567(user)." Note that Access Code 109 is automatically dialed as quick burst, say .75 second, after a short pause, perhaps .25 second. The user will hear the code dialed, but will be able to dial the complete long distance number at a natural pace.

Suppose instead that the user wished to defeat the Autodialer and dial "1-411" without an access code. The Autodialer is at Wait State 20. The user presses "1" and

holds it for a second or so. The Autodialer detects the DTMF signal and proceeds to Action 21 and Wait State 22. Digit Duration timer 106 expires while the user is pressing "1", and the Autodialer proceeds to Action 26 without dialing Access Code 109.

Suppose that the user caused a FAX machine to dial a long distance number. If the FAX machine dials the complete number without pause, then when the Autodialer reaches Wait State 24, it will exit because the DTMF signal corresponding to the digit after the "1" will be detected before Digital Interval Timer 107 expires and Access Code 109 will not be dialed. Thus, the Autodialer will not conflict with the FAX Machine. However, if the user wishes to program a pause after the "1" dialed by the FAX machine (or any other speed dialer), then the Autodialer will dial Access Code 109 during the pause.

Battery-powered Embodiment

The embodiment shown in Figure 2A is an evolution of that depicted in Figure 1A, with the action of a Transient Detector 113, which continuously monitors Telephone Loop 101 for any voltage transient that might indicate that a telephone extension has been taken off hook, and a Power Control 115, which turns power on and off to the rest of the electronic components. Another addition is a First Digit Timer 117, and an electronic Logic 116 which has additional control functions associated with battery operation. A Power Source 114 is a battery capable of operating all of the electronics.

A Diode Bridge 111 is connected to Telephone Loop 101 to provide a polarity-corrected voltage output referenced to the digital ground of the Autodialer. This output is

connected to Transient Detector 113. Transient Detector 113 comprises resistors and capacitors to filter the transients, and a transistor or other means to convert a filtered transient into a useful logic pulse output. This output causes Power Control 115 to turn power on. An output from Logic 116 causes Power Control 115 to turn power off.

5 Since this embodiment is battery powered, there is no requirement to provide isolation from the AC mains and earth ground (as long as the device is housed in an insulated case). For the same reason, longitudinal balance can be maintained without a line transformer. Therefore, AC Coupling 112 is the form of capacitive coupling which is smaller and lighter.

10 The method of the embodiment of Figure 2A is depicted in Figure 2B. It is similar to Figure 1B except that Wait State 28 and Actions 29, 31, and 32 have been added, and Action 26 and Wait State 27 have been removed. Wait State 28 is the power-off idle state. Also, since Transient Detector 113 signals the beginning of a call, there is no need to wait for the user to finish dialing the previous number.

15 When the user picks up a telephone to dial, Wait State 28 exits due to the output from Transient Detector 113, and Action 32 turns power on the rest of the electronics. Immediately, Action 29 starts First Digit Timer 117. If Wait State 20 exits because First Digit Timer 117 expired; then, the user did not dial a number, and might have picked up the telephone to answer a call. The Autodialer then proceeds to Action 31 and Wait State
20 28, and Power Control 115 disconnects power to the rest of the electronics.

 On the other hand, if Wait State 20 exits because a DTMF signal was detected by DTMF Receiver 104, then the operation of the Autodialer proceeds as in the Basic

Embodiment. However, this embodiment then proceeds to Action 31, "Turn Off Power," rather than wait for the user to finish dialing.

Preferred Embodiment

5 The preferred embodiment is depicted in Figure 3A.

A DTMF Transceiver 119 comprises both a DTMF transmitter and receiver with a microprocessor-compatible interface. The Teltone M8888 is a suitable IC.

A Microprocessor 110 is an inexpensive microprocessor with an Analog to Digital Converter input and capable of a very low-power "sleep" mode, such as the PIC16C72
10 manufactured by Microchip Technology Inc. of Chandler, Arizona.

A Low Pass Filter 118 is connected between Diode Bridge 111 and Microprocessor 110's Analog to Digital Converter Input. Low Pass Filter 118 is a combination of resistors and capacitors designed to pass DC voltages and low-frequency ringing signals.

15 Microprocessor 110 receives battery power continuously, but spends most of the time in "sleep" mode. The PIC16C72 is capable of a sleep mode that drains a few microamperes of supply current. Transient Detector 113 is connected to an input of Microprocessor 110 that is capable of bringing the processor out of sleep mode. Microprocessor 110 uses an output pin to operate Power Control 115, which in turn
20 controls battery power to the rest of the electronics, primarily DTMF Transceiver 119.

Refer to the method depicted in figure 3B, which describes the logic flow of the software program executed by Microprocessor 110. Note that the timers referred to in

Actions 21, 23, and 29 are here implemented using software timing loops or a hardware timer internal to Microprocessor 110. The Autodialer is idle, and Microprocessor 110 is in sleep mode in Wait State 28. A change in voltage on Telephone Loop 101 is detected by Transient Detector 113 and brings the processor out of sleep mode. Wait State 28 thus exits and Action 32 turns on power to the rest of the electronics. Action 30 "Measure Off-Hook Voltage," occurs when Microprocessor 110's Analog to Digital Converter samples and measures the DC voltage on Telephone Loop 101. If a user is initiating a call, this voltage will represent the off-hook voltage of the loop under present conditions with the user's telephone instrument. If later measurements of DC voltage are at least 8V above this initial measurement, then, it is assumed that the user has hung up. (This minimum voltage rise is calculated using the minimum loop current drawn by a telephone of 20 mA and a minimum loop resistance in practice of 400 ohms).

The Autodialer now proceeds to Action 29, "Start First Digit Timer," and to Wait State 20. During Wait State 20, the microprocessor continues to sample and measure the voltage on Telephone Loop 101, as seen through Diode Bridge 111. In this way ringing can be detected as a large AC voltage, and upon completion Wait State 20 will exit and proceed to Action 31, Turn Off Power, and back to Wait State 28. Wait State 20 will exit in the same way if the voltage measurement indicates on hook, or if the first digit timer expires. Any of these exits indicates that the user is not going to dial a number.

On the other hand if Wait State 20 exits because a DTMF signal was detected, then the Autodialer proceeds to Action 21, "Start Digit Duration Time," and continues as in Figure 2B.

Other Embodiments

As noted above, Programmed Long Distance Access Code 109 is a means for the invention to store and retrieve the access code; said means may be one of several forms.

- 5 Manual switches, such as the “thumbwheel” type, would allow the user to easily enter or change codes at any time, especially if only the necessary digits of the code have corresponding switches. For example, three switches corresponding to three usual digits must be mounted immediately to the right of a preprinted “1010,” so that the user immediately sees that the code us the familiar “1010xxx,” where the “xxx” corresponds
- 10 to the chosen digits programmed into the switches.

Access Code 109 might also be preset before the consumer receives the autodialer. In this case, Access Code 109 could be an internal electronic element, internal switches of the “DIP switch” type , or internally coded into the instructions of Microprocessor 110 so that the user can not readily change the access code. An important

15 commercial application for this would be to distribute to consumers preset autodialers in order to promote a particular long distance service.

- Other expedient means of implementing Access Code 109 are conceivable. For example, the invention might be built into a telephone instrument in which case Access Code 109 might be entered into an electronic memory element by means of the telephone
- 20 dialing keypad.

The present invention comprises any convenient electronic means of sending and receiving DTMF digits, a means of coupling said digits to an analog telephone loop

without drawing loop current, electronic logic and timers of any convenient form to detect an initial "1" digit (signifying a long distance number), a means of storing and retrieving a programmed access code, and electronic logic to sequence the access code through the DTMF sender in response to an initial; "1" digit. It will be apparent that the present

5 invention provides its user with a means of remembering and dialing a desired long distance access code with no inconvenience, and after a trivial installation. It should also be apparent that the judicious use of electronic timers in any form allows the user to easily defeat the Autodialer when it is desired to dial a non-long distance number such as "1411." It should also be apparent that a further use of timers allows preprogrammed
10 "speed dialers" and modems to defeat the Autodialer simply by dialing more rapidly than manual dialing, or to enable the Autodialer by using the "Pause" found in nearly all dialers and modems.

It will be recognized by those skilled in the art that modifications and variations to the invention as disclosed can be made without departing from the spirit and scope of the
15 invention. While the above descriptions contain many specifics, these should not be construed as limitations on the scope of the invention, but rather as examples effective and inexpensive embodiments. Other variations are possible, for example using different properties of the telephone line to determine the start of a telephone call such as the presence of dialtone to indicate when to monitor for the first digit or the change in voltage
20 across the line in conjunction with a test for ringing voltage to distinguish originating from answering a call. The present invention does not depend upon the means chosen. The advance in the art represented by the present invention lies in what happens after the

[illegible]